

LEGRAND 180° SENZOR DE MISCARE -IP40 -8 M -MONTAJ INCASTRAT -CUOUT OVERRIDE -PIR -CARDBOARD

Caracteristici tehnice
2-wire motion sensors, without neutral
IR detection
Accepted Putere by lamp type:
LEDs: 3 to 100 W
compact fluorescent: 3 to 100 W
LEDs, CFLs, Halogen, fluo tubes with ferromagnetic or electronic transformer: 3 to 250 VA
halogen 230 V, incandescent: 3 to 250 W
For LED and compact fluorescent lamps
If several sensors are installed on the same circuit, the minimum load changes: refer to the technical sheet
Possibility to install up to 3 sensors in parallel
Time delay setting from 10 s to 10 min
Light level threshold setting from 5 lux to 1275 lux
Standby Consum : 0.2 W
Sensor without override
Cardboard
Range 8 m
Recommanded fixing height: 1.2 m
2-wire without neutral
Light level threshold: 5 to 1275 lux
Adjustable time delay: 10 s to 10 min
Standby Consum: 0.2 W
Caracteristici generale
Mosaic™ Programme mechanisms - motion and presence sensors
All sensors are compatible with any lamp - Detection field: 120°
Detection range: 8 m

Recommended installation height: 1.20 m
Integrated self-protection against overloads and short-circuits.
2 module
Pret: 504,92 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/1800-senzor-de-miscare-ip40-8-m-montaj-incastrat-cuout-override-pir-cardboard-221715