

LEGRAND 2-WIRE SENZOR DE MISCARE MOSAIC - CUOUT NEUTRAL - CU OVERRIDE - ALB

Caracteristici tehnice
2-wire motion sensors, without neutral
IR detection
Accepted Putere by lamp type:
LEDs: 3 to 100 W
compact fluorescent: 3 to 100 W
LEDs, CFLs, Halogen, fluo tubes with ferromagnetic or electronic transformer: 3 to 250 VA
halogen 230 V, incandescent: 3 to 250 W
For LED and compact fluorescent lamps
If several sensors are installed on the same circuit, the minimum load changes: refer to the technical sheet
Possibility to install up to 3 sensors in parallel
Time delay setting from 10 s to 10 min
Light level threshold setting from 5 lux to 1275 lux
Standby Consum : 0.2 W
Sensor with override
Mosaic
Without neutral
Caracteristici generale
Mosaic™ Programme mechanisms - motion and presence sensors
All sensors are compatible with any lamp - Detection field: 120°
Detection range: 8 m
Recommended installation height: 1.20 m
Integrated self-protection against overloads and short-circuits.
2 module
Pret: 557,54 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/2-wire-senzor-de-miscare-mosaic-cuout-neutral-cu-override-alb-222222