

LEGRAND 360° SENZOR DE MISCARE MOSAIC - PIR - •Ø 8 M - CU 2 A CONTACT PENTRU HVAC- ALB

Caracteristici tehnice
Ideal for offices
PIR ceiling-mounting Lighting Management sensor, 360°
Range O8 m
3-wire with neutral
Optimum distance between 2 sensors: 6 m
Standby Consum: 0.8 W
Fix directly to a false ceiling with mounting claws (included) or installed in a Batibox box, depth 50 mm
Can be surface-mounted in ceiling using accessory Cat.No 0 488 75
With an additional 2 A contact for HVAC control, based on presence data
Caracteristici generale
Lighting Management sensors for 1 circuit - Lighting Management sensors for working areas with natural light
Check presence and light level continuously, switch off when there is sufficient natural light
Occupancy mode (automatic switch-on/off factory setting)
Can be used with push-button Cat.No 0 770 40 (or illuminated push-button Cat.No 0 770 33) for vacancy mode (manual switch-on and manual or automatic switch-off)
Infrared and ultrasonic Lighting Management sensors for workplaces, allowing precise presence detection as soon as the wave transmitted by the sensor is modified (for example, by hand movement on a keyboard)
Precise on-site adjustment using configuration tool
Pret: 425,72 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/3600-senzor-de-miscare-mosaic-pir-oe-8-m-cu-2-a-contact-pentru-hvac-alb-222280