

LEGRAND AUTOMATIC TRANSFER SWITCH CONTROL UNITS PENTRU ADVANCED MANAGEMENT OF 2 CIRCUIT BREAKERS - 6 INPUTS 7 OUTPUTS

Caracteristici tehnice
Automatic transfer switch control units
For standard management of 2 circuit breakers
6 programmable digital inputs and 7 programmable relay outputs
Can be equipped with maximum 2 plug-in module between:
extension module Cat.No 4 226 90/91/92
opto-isolated RS485 communication interface Cat.No 4 226 89
LCD display
IR communication port on the front panel for connection of USB or WiFi module Cat.No 4 226 87/88
Can be configured with the help of front panel touch keys or of the Legrand dedicated software
Tensiune de alimentare: 12-24 V=
110-240 V~
IP40
IP40
Configuration software available for download via e-catalogue ACU Configurator app for smartphone and tablet available on Apple Store and Google Play
configuration software available for download via E-catalogue
Caracteristici generale
Automatic transfer switch control units
They can control transfer switching between two sources, manage generator start/stop, control single phase, two-phase and three-phase networks, control phase-phase and phase-neutral Tensiunes
For DPX³ and DMX³ circuit breakers and CTX³ contactors
Pret: 7.386,98 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/automatic-transfer-switch-control-units-pentru-advanced-management-of-2-circuit-breakers-6-inputs-7-outputs-222793