



## **LEGRAND\* AUTOTEST/ADRESSABLE LED LAMPA DE EMERGENTA TWINSPO - 2** **X 750 LM - 1H**

### Caracteristici tehnice

Autotest and addressable LED spotlight luminaire - Non-Maintained (NM)

2 x 750 lm – 1h

Incorporates an automatic self-testing system that checks periodically the emergency lighting function:  
weekly test of emergency lighting mode

quarterly test of battery duration

Tests result is visible via 2 signalling LEDs (green = OK and yellow = defective) on the luminaire

Addressable function is activated by setting an ID on each luminaire with infrared configuration tool (Cat.No 0 626 10) and wiring a complementary BUS line

Operating state of all addressable luminaires can be centralized by the control interface Cat.No 0 626 00 and monitored on a local touch screen controller (Cat.No 0 626 01), or with the building's plan on Legrand Vision System (L.V.S. 2) PC software

### Caracteristici generale

LED Twinspot emergency lighting luminaires

High performance LED non maintained emergency lighting luminaires

Certified to IEC and EN 60598-2-22 standards

High Putere LEDs spotlights with optimized lighting distribution

Low Consum electronic switching Tensiune de alimentare

High capacity terminals: 2 x 2.5 mm<sup>2</sup> - IP 55 - IK 07

Duration: 1, 2 and 3 hours. Ni-Cd batteries. Recharge time: 24h

Green charge indicator with high luminosity LED, to improve visibility from the floor when high installation

Tensiune de alimentare: 230 V~ ± 10% - 50/60 Hz. Class II

Rest mode with remote control device Cat.No 0 039 01 to avoid battery discharge in case of voluntary Putere cut

Surface mounting installation with 4 wall-mounting lugs (Cat.No 0 358 02, supplied) or 4 screws (not supplied)

Pret: 3.314,06 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/autotest-adressable-led-lampa-de-emergenta-twinspot-2-x-750-lm-1h-222797>