

LEGRAND* AUTOTEST/ADRESSABLE LUMINAIRES U34 LED - 1H DURATION CU OPAL DIFFUSER - 450 LM

Caracteristici tehnice
Autotest and addressable luminaires - Maintained/Non-maintained (M/NM)
Autotest/addressable luminaires incorporate an automatic self-testing system
Tests result is visible on 2 signalling LEDs (green-OK and yellow-defective)
Addressable function is activated by setting an ID on each luminaire with infrared configuration tool (Cat.No. 0 626 10) and wiring a complementary BUS line
Operating state of all addressable luminaires can be centralized by the control interface (Cat. No. 0 626 00) and monitored on a local touch screen controller (Cat.No 0 626 01), or with the building's plan on Legrand Vision System (LVS2) PC software Cat.No 0 626 02
1 h duration with transparent diffuser
450 lm - 1h (LEDs)
Caracteristici generale
U34LED environment friendly - indoor self-contained emergency lighting luminaires LED
LED Maintained/Non-maintained units
High Putere LEDs with specially designed lenses optimizing the lighting distribution
IP 42 - IK 07 - Class II
Tensiune de alimentare: 230 V ± 10% - 50/60 Hz
Very low Consum switching Tensiune de alimentare - Fully recyclable after removing
Environment friendly Ni-MH batteries
Removable plug-in plate to ease installation and maintenance
Automatic terminals with high capacity: 2 x 2.5 mm²
Charge monitor with a green LED
Can be equipped with metallic protection grids Cat.Nos 0 626 92/93
Pret: 804,37 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/autotest-adressable-luminaires-u34-led-1h-duration-cu-opal-

diffuser-450-lm-222799