



## **LEGRAND\* AUXILIARY OR FAULT SIGNALLING CONTACT DX<sup>3</sup> - 6 A 250 V~ - 0.5 MODULE**

### Caracteristici tehnice

Signalling auxiliaries fork busbar adapted

To fit on the Stanga-hand side of DX<sup>3</sup> and TX<sup>3</sup> devices

Maximum number of auxiliaries per device:

3 signalling auxiliaries or

2 signalling auxiliaries + 1 remote tripping auxiliary

Allow insertion of the supply busbar, top side

No tool required for joining together the auxiliary and the main device.

No tool required for joining together the auxiliary and the main device.

Auxiliary contact

6 A - 250 V~ (changeover switch)

For MCBs, RCBOs, RCCBs, isolating switch or remote trip isolating switch

Indicates the position of the contacts of its associated device

Fault signalling contact

6 A - 250 V~ (changeover switch)

For MCBs, RCBOs, RCCBs

Allows the choice between the two functions

Numar de module : 0.5

Caracteristici generale

Signalling, remote tripping auxiliaries and motorised controls DX<sup>3</sup>

Pret: 86,20 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/auxiliary-or-fault-signalling-contact-dx3-6-a-250-v-0-5-module-222830>