


LEGRAND CLEMA SIR VIKING 3 - SPRING - 1 CONNECT - 1 ENTRY/1 OUTLET - PITCH 6 - ALBASTRU

Caracteristici tehnice
Connecting
Grey for standard circuit, blue for neutral conductor, orange for circuit not broken by the master isolating device
1 connection - 2 wires - 1 entry/1 outlet
Built-in end cap
Colour : Blue
Nominal cross-section : 4 mm²
Capacity - Rigid wire : 0.5 to 6 mm²
Capacity – Flexible wire : 0.5 to 4 mm²
Flexible wire with ferrule : 0.5 to 4 mm²
Pitch : 6 mm
Caracteristici generale
Viking™ 3 terminal blocks with spring connection - for copper cables
Screwless connection system, stainless steel spring type
Used to make the electrical connection between 2 rigid copper wires, or flexible copper wires with or without ferrules
Direct tool-free insertion of a rigid wire or flexible wire with ferrule, up to 6 mm pitch
2 areas for automatic insertion bridging combs (upper level only for 2-level blocks)
For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm
Pret: 7,54 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/clema-sir-viking-3-spring-1-connect-1-entry-1-outlet-pitch-6-albastru-224105