

LEGRAND CLEMA SIR VIKING 3 - SPRING - PENTRU CONDUCTOR - 1 CONNECT -24 WIRES -PITCH 10

Caracteristici tehnice
For protection conductor
Metal base
Screwless fixing on rail
PEN from 10 mm²
1 connection - 2 wires - 1 entry/1 outlet
Colour : Green/yellow
Nominal cross-section : 10 mm²
Capacity - Rigid wire : 0.75 to 10 mm²
Capacity – Flexible wire : 0.75 to 10 mm²
Flexible wire with ferrule : 0.75 to 10 mm²
Pitch : 10 mm
Caracteristici generale
Viking™ 3 terminal blocks with spring connection - for copper cables
Screwless connection system, stainless steel spring type
Used to make the electrical connection between 2 rigid copper wires, or flexible copper wires with or without ferrules
Direct tool-free insertion of a rigid wire or flexible wire with ferrule, up to 6 mm pitch
2 areas for automatic insertion bridging combs (upper level only for 2-level blocks)
For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm
Pret: 48,10 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/clema-sir-viking-3-spring-pentru-conductor-1-connect-24-wires-pitch-10-224134