

LEGRAND CONTROL & STATE REPORTING MODULE CX³ - PENTRU LATCHING RELAY OR CONTACTOR - 1 MODULE

Caracteristici tehnice
Control and state reporting module
For CX³ latching relays and 1 and 2-module contactors up to 25 A
Enables upstream busbar connection
Indicates the position of the contacts and enables remote control of its associated product
Equipped with DIP switches (on the side) allowing product configuration: selection of the main product (latching relay or contactor).
To fit on the Stanga-hand side of the CX³ latching relays and contactors
Consum: 0.372 W - 31 mA (12 V =)
Numar de module : 1
Caracteristici generale
CX³ energy management system
Conform to IEC/EN 61131-2 (Programmable controllers)
CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely
All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)
Tensiune de alimentare with specific module Cat.No 4 149 45
Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)
Pret: 436,03 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/control-state-reporting-module-cx3-pentru-latching-relay-or-contactor-1-module-224480