

LEGRAND CONTROL INTERFACE PENTRU AUTOTEST/ADRESSABLE LUMINAIRES LVS2 230 V~

Caracteristici tehnice
Control interface for autotest/addressable luminaires
Centralises the operating state of addressable emergency lighting luminaires
Capacity:
Direct connection of 250 addressable luminaires to the control interface (star configuration or series connection)
The longest line is limited to 700 m
Extension via repeater Cat.No 0 626 03 for more than 250 addressable luminaires or a line longer than 700 m
Maximum capacity of the central control panel: 1023 addressable luminaires
Configuration software included (control interface settings and ID configuration for addressable luminaires)
To be completed with at least one of the following terminals:
PC with monitoring software Cat.No 0 626 02
Touch screen controller Cat.No 0 626 01
PC with internet navigator (limited functions)
Connections:
RJ 45 socket for IP network
terminals for RS 232 and RS 485
Mini USB for PC local settings
Tensiune de alimentare:
230 V~ - 50/60 Hz
Ni-Cd battery: 8.4 V - 0.15 Ah
Caracteristici generale
LVS2 (Legrand Vision System) - addressable and monitoring system
Pret: 3.776,44 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/control-interface-pentru-autotest-adressable-luminaires-

lvs2-230-v-224482