



## **LEGRAND CONTROL INTERFACE PENTRU AUTOTEST/ADRESSABLE LUMINAIRES** **LVS2 230 V~**

Caracteristici tehnice

Control interface for autotest/addressable luminaires

Centralises the operating state of addressable emergency lighting luminaires

Capacity:

Direct connection of 250 addressable luminaires to the control interface (star configuration or series connection)

The longest line is limited to 700 m

Extension via repeater Cat.No 0 626 03 for more than 250 addressable luminaires or a line longer than 700 m

Maximum capacity of the central control panel: 1023 addressable luminaires

Configuration software included (control interface settings and ID configuration for addressable luminaires)

To be completed with at least one of the following terminals:

PC with monitoring software Cat.No 0 626 02

Touch screen controller Cat.No 0 626 01

PC with internet navigator (limited functions)

Connections:

RJ 45 socket for IP network

terminals for RS 232 and RS 485

Mini USB for PC local settings

Tensiune de alimentare:

230 V~ - 50/60 Hz

Ni-Cd battery: 8.4 V - 0.15 Ah

Caracteristici generale

LVS2 (Legrand Vision System) - addressable and monitoring system

Pret: 3.747,94 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/control-interface-pentru-autotest-adressable-luminaires->

