



LEGRAND* CAPAC VALENA LIFE - SENZOR DE MISCARE CU OVERRIDE - CU MECHANISM - IVORY

Caracteristici tehnice

Motion sensors

All sensors are compatible with any type of lamp

Detection field 120°

Detection range 8 m

Integrated self-protection against overloads and short-circuits

Motion sensors without neutral, with override

The sensor can be forced to ON, Automatic or OFF mode using a 3-position slider

Accepted Putere by lamp type:

LEDs 3 W to 100 W (If several sensors are installed on the same circuit, the minimum load increases)

compact fluorescent 3 W to 100 W (If several sensors are installed on the same circuit, the minimum load increases)

LEDs, CFLs, Halogen, fluorescent tubes with ferromagnetic or electronic ballast: 3 VA to 250 VA

230 V halogen, incandescent: 3 W to 250 W

Up to 3 sensors can be connected in parallel

Possibility of additional remote manual control with push-button

Time delay setting from 10 s to 10 min.

Light level threshold setting from 5 lux to 1275 lux

Standby Consum: 0.02 W

Ivory

Caracteristici generale

Valena™ Life - motion sensors, roller blind controls and thermostats with cover plate

Valena In'Matic mechanisms supplied with cover plates and support frames

To be equipped with plates

Supplied with mounted dust protection transparent shield

Flowpack packaging: robust protection to ensure optimum operation

Pret: 598,14 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/capac-valena-life-senzor-de-miscare-cu-override-cu-mechanism-ivory-224992>