



### **LEGRAND DEVICE PENTRU EMERGENCY EXIT - 1 NO/NC - 5 A - 24 V= - RAL 6016**

Caracteristici tehnice

Manual call points (MCP)

IP 30 - IK 07

Surface-mounting or Montaj incastrat (IP 30)

Dimensions: 90x90x57 mm (surface-mounting with its base) or 90x90x24 mm (Montaj incastrat with flush boxes for wiring devices - drilling diameter 67 mm - for 60 mm fixing centres)

Can be fitted on trunking Cat. Nos 0 104 63/64, 35x105 mm or 50x105 mm, with the universal support Cat. No 0 109 13

Call by pressing the membrane (pressure 2.5 kg) with clear display of the call position

Reset on front of device, with special key Cat. No 0 380 38 (supplied with the product)

Possibility to add an optional mechanical status indicator Cat. No 1 380 93 to provide additional signalling

Can receive a sealable cover Cat.No 0 380 97

Devices for emergency exit (DCMIS)

Allow the immediate release of an exit door normally closed by an electromagnetic lock

Color of the mechanical enclosure: green RAL 6016

DCMIS - 1 contact

Equipped with 1 NO/NC contact – 5 A – 24 VDC

Caracteristici generale

Safety boxes 90 series - for fire detection and fire alarm system, emergency exit, extinguishing system, remote switching

Pret: 227,91 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/device-pentru-emergency-exit-1-no-nc-5-a-24-v-ral-6016-225288>