

LEGRAND* LAMPA DE EMERGENTA B65 - AUTOTEST/ADDRESS MAINT./NON MAINT. - 100 LM - 3H - LED

Caracteristici tehnice
Autotest and addressable luminaires - Maintained/Non-maintained (M/NM)
Autotest/addressable luminaires incorporate an automatic self-testing system in order to check emergency lighting
Tests result is visible on 2 signalling LEDs (green-OK and yellow-defective)
Addressable function is activated by setting an ID on each luminaire with configuration tool (Cat.No 0 626 10) and wiring a complementary BUS line
Operating state of all addressable luminaires can be centralized by the control interface (Cat.No 0 626 00) and monitored on a local touch screen controller (Cat.No 0 626 01), or with the building’s plan on Legrand Vision System (LVS2) PC software Cat.No 0 626 02
These Maintained luminaires can also operate in Non-maintained mode according to the wiring of normal lighting
100 lm - 3h (LEDs)
Caracteristici generale
B65 LED - weatherproof self-contained emergency lighting luminaire LED
Weatherproof LED maintained and non-maintained units
Certified to IEC and EN 60598-2-22 standards
High Putere LEDs. IP 65 - IK 07
Plug-in base to ease fixing, cabling and connection
Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries. Recharge time: 24 hours
Charge monitor with a green LED. Tensiune de alimentare: 230 V ± 10%- 50/60 Hz. Class II
High-capacity screw terminals (2 x 2.5mm²)
3 flexible cable entries for O16, 20 and 25 mm tubes
Can be equipped with metallic protection grids Cat.Nos 0 626 90/92
Pret: 755,59 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lampa-de-emergenta-b65-autotest-address-maint-non-maint-100-lm-3h-led-225964