

LEGRAND* LAMPA DE EMERGENTA U21 - STANDARD NON MAINTAINED - 3 H - 90 LM - LED

Caracteristici tehnice
Standard luminaires
Require normal lighting manual switching off in order to test emergency lighting
Non-maintained (NM)
90 lm - 3h (LEDs)
Caracteristici generale
U21 LED - indoor self-contained emergency lighting luminaires LED
LED maintained and Non-maintained units
Certified to IEC and EN60598-2-22 standards
High Putere LEDs
IP 42 - IK 04. Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries
Recharge time: 24 hours. Charge monitor with a green LED
Tensiune de alimentare: 230 V~ ±10% - 50/60Hz - Class II
High capacity screw terminals (2 x 2.5 mm²)
To install a full IP 65 solution, add IP 65 weatherproof box Cat.No 6 616 16
Montaj incastrat in dry partitions (ceiling and wall): add Montaj incastrat frame Cat.No 6 617 20. Montaj incastrat in masonry (brick or concrete wall): add both Montaj incastrat box Cat.No 0 617 21 and Montaj incastrat frame Cat.No 6 617 20
Can be equipped with metallic protection grids Cat.Nos 0 626 90/92
Pret: 214,52 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lampa-de-emergenta-u21-standard-non-maintained-3-h-90-lm-led-225980