



## **LEGRAND EMERGENCY SHUTDOWN CONTROL DEVICE - 2 NO/NC - 5 A - 24 V= - RAL 9003**

Caracteristici tehnice

Manual call points (MCP)

IP 30 - IK 07

Surface-mounting or Montaj incastat (IP 30)

Dimensions: 90x90x57 mm (surface-mounting with its base) or 90x90x24 mm (Montaj incastat with flush boxes for wiring devices - drilling diameter 67 mm - for 60 mm fixing centres)

Can be fitted on trunking Cat. Nos 0 104 63/64, 35x105 mm or 50x105 mm, with the universal support Cat. No 0 109 13

Call by pressing the membrane (pressure 2.5 kg) with clear display of the call position

Reset on front of device, with special key Cat. No 0 380 38 (supplied with the product)

Possibility to add an optional mechanical status indicator Cat. No 1 380 93 to provide additional signalling

Can receive a sealable cover Cat.No 0 380 97

Emergency shutdown control devices

Color of the mechanical enclosure: white RAL 9003

Emergency shutdown control device - 2 contacts

Equipped with 2 NO/NC contacts – 5 A – 24 VDC

Second contact can be used to trigger a technical alarm

Caracteristici generale

Safety boxes 90 series - for fire detection and fire alarm system, emergency exit, extinguishing system, remote switching

Pret: 202,48 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/emergency-shutdown-control-device-2-no-nc-5-a-24-v-ral-9003-226000>