

LEGRAND* FLUSH MOUNTING FRAME - PENTRU MONTAJ IN U21 LUMINAIRES ON DRY PARTITION

Caracteristici tehnice
Accessories
Montaj incastrat frame for dry partition
Caracteristici generale
U21 LED - indoor self-contained emergency lighting luminaires LED
LED maintained and Non-maintained units
Certified to IEC and EN60598-2-22 standards
High Putere LEDs
IP 42 - IK 04. Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries
Recharge time: 24 hours. Charge monitor with a green LED
Tensiune de alimentare: 230 V~ ±10% - 50/60Hz - Class II
High capacity screw terminals (2 x 2.5 mm²)
To install a full IP 65 solution, add IP 65 weatherproof box Cat.No 6 616 16
Montaj incastrat in dry partitions (ceiling and wall): add Montaj incastrat frame Cat.No 6 617 20. Montaj incastrat in masonry (brick or concrete wall): add both Montaj incastrat box Cat.No 0 617 21 and Montaj incastrat frame Cat.No 6 617 20
Can be equipped with metallic protection grids Cat.Nos 0 626 90/92
Pret: 24,32 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/flush-mounting-frame-pentru-montaj-in-u21-luminaires-on-dry-partition-226777