



LEGRAND* INTRERUPATOR GENERAL TIP USOL 1600 - S1 ELECTRONIC RELEASE - 3P - ICU 36 KA (400 V~) - IN 800 A

Caracteristici tehnice

MCCBs electronic release S1 fixed version

Adjustment of Ir, Isd

Instantaneous protection If = 20 kA

Green indicator lamp

Connector for test unit

Dynamic selectivity

4P version: adjustment of neutral on front panel

Breaking capacity Icu 36 kA (400 V~)

3P

In : 800 A

Caracteristici generale

DPX³ 1600 - S1 electronic release MCCBs from 630 to 1600 A

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Can be used with residual current relays

Do not accept DPX³ electronic interface for Modbus Cat.No 4 210 75

Supplied complete with:

connection plates for bars

insulated shields (phase barriers)

Conform to IEC 60947-2 - Sealable adjustment

Can be mounted on plate in XL³ cabinets and enclosures

Pret: 7.825,99 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol-1600-s1-electronic-release-3p-icu-36-ka-400-v-in-800-a-228086>