www.MATERIALE ELECTRICE.ro
Consiliere specializata



LEGRAND* INTRERUPATOR GENERAL TIP USOL ECHIPAT CU CONTOR + E.L.C.BS - INTRERUPATOR GENERAL TIP USOL 250 - ICU 25 KA - 4P - 250 A

Caracteristici tehnice
MCCBs with energy metering central unit and electronic earth leakage module - fixed version
Protection against overloads:
lr adjustable from 0.4 to 1 x ln
tr adjustable from 3 to 15s
Protection against short circuits:
lsd adjustable from 1.5 to 10 x lr
tsd adjustable from 0 to 0.5s
Equipped with earth leakage module with LCD screen
Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A
Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)
Integrated energy metering central unit with LCD screen; currents, Tensiune, frequency, Putere, energy and harmonics
Breaking capacity Icu 25 kA (400 V~)
4P
In : 250 A
Caracteristici generale
DPX³ 250 electronic release - MCCBs from 40 to 250 A
Can be mounted on rail or on plate in XL³ cabinets and enclosures
MCCBs for switching, control isolation and protection of low Tensiune electrical lines
Supplied with fixing screws, connection plates for bars and cable lugs and insulated shields (phase barriers)
Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable and with DPX³ 160 and 250 common auxiliaries and accessories
Conform to IEC 60947-2
Pret: 4.115,22 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/intrerupator-general-tip-usol-echipat-cu-contor-e-l-c-bs-intrerupator-general-tip-usol-250-icu-25-ka-4p-250-a-228574