



**LEGRAND* INTRERUPATOR GENERAL TIP USOL125 HP THERMAL MAGNETIC
MCCB CU ELECTRONIC EARTH LEAKAGE MODULE FIXED VERSION - 36KA - 4P -
25A**

Caracteristici tehnice

MCCBs with electronic earth leakage module - fixed version

Thermal adjustable from 0.8 to 1 In

Magnetic fixed at 10 In (fixed at 400 A for In from 16 A to 40 A)

Equipped with earth leakage module

Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A

Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0 s)

Breaking capacity Icu 36 kA (400 V~)

4P

In : 25 A

Caracteristici generale

DPX³ 125 HP - thermal magnetic release MCCBs from 16 to 125 A - fixing on plate

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Furnizat cu: screws for connections, fixing screws and insulated shields (phase barriers)

Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable

Conform to IEC 60947-2

Sealable adjustment

Can be mounted on plate in XL³ and XL³ S cabinets and enclosures

Pret: 1.565,22 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol125-hp-thermal-magnetic-mccb-cu-electronic-earth-leakage-module-fixed-version-36ka-4p-25a-228719>