



LEGRAND* INTRERUPATOR GENERAL TIP USOL125 HP THERMAL MAGNETIC RELEASE MCCB FIXED VERSION - PUTERE DE RUPERE 100KA - 3P - 63A

Caracteristici tehnice

MCCBs - fixed version

Thermal adjustable from 0.8 to 1 In

Magnetic fixed at 10 In (fixed at 400 A for In from 16 A to 40 A)

Breaking capacity Icu 100 kA (400 V~)

3P

In : 63 A

Caracteristici generale

DPX³ 125 HP - thermal magnetic release MCCBs from 16 to 125 A - fixing on plate

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Furnizat cu: screws for connections, fixing screws and insulated shields (phase barriers)

Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable

Conform to IEC 60947-2

Sealable adjustment

Can be mounted on plate in XL³ and XL³ S cabinets and enclosures

Pret: 660,26 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-tip-usol125-hp-thermal-magnetic-release-mccb-fixed-version-putere-de-rupere-100ka-3p-63a-228743>