LEGRAND* INTRERUPATOR GENERAL TIP USOL125 HP THERMAL MAGNETIC RELEASE MCCB FIXED VERSION - PUTERE DE RUPERE 36KA - 4P - 20A

Caracteristici tehnice
MCCBs - fixed version
Thermal adjustable from 0.8 to 1 In
Magnetic fixed at 10 In (fixed at 400 A for In from 16 A to 40 A)
Breaking capacity Icu 36 kA (400 V~)
4P
In : 20 A
Caracteristici generale
DPX³ 125 HP - thermal magnetic release MCCBs from 16 to 125 A - fixing on plate
Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines
Can be fitted with auxiliaries
Furnizat cu: screws for connections, fixing screws and insulated shields (phase barriers)
Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable
Conform to IEC 60947-2
Sealable adjustment
Can be mounted on plate in XL³ and XL³ S cabinets and enclosures
Pret: 666,40 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/intrerupator-general-tip-usol125-hp-thermal-magnetic-release-mccb-fixed-version-putere-de-rupere-36ka-4p-20a-228768