



LEGRAND* INTRERUPATOR GENERAL TIP USOL250 HP S1 ELECTRONIC RELEASE **MCCB FIXED VERSION - PUTERE DE RUPERE 36KA - 3P - 40A**

Caracteristici tehnice

MCCBs - fixed version

Protection against overloads:

I_r adjustable from 0.4 to 1 x I_n

t_r adjustable from 3 to 15s

Protection against short circuits:

I_{sd} adjustable from 1.5 to 10 x I_r

t_{sd} adjustable from 0 to 0.5s

Breaking capacity I_{cu} 36 kA (400 V~)

3P

I_n : 40 A

Caracteristici generale

DPX³ 250 HP - S1 electronic release MCCBs from 40 to 250 A - fixing on plate

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Furnizat cu: screws for connection fixing screws, connection plates for bars and cable lugs and insulated shields (phase barriers)

Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable

Can be mounted on plate in XL³ and XL³ S cabinets and enclosures

Conform to IEC 60947-2

Pret: 2.225,48 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-tip-usol250-hp-s1-electronic-release-mccb-fixed-version-putere-de-rupere-36ka-3p-40a-228834>