



**LEGRAND* INTRERUPATOR GENERAL TIP USOL250 HP THERMAL MAGNETIC
MCCB CU ELECTRONIC EARTH LEAKAGE MODULE FIXED VERSION - 36KA - 4P -
16A**

Caracteristici tehnice

MCCBs with electronic earth leakage module - fixed version

Thermal adjustable from 0.8 to 1 In

Magnetic:

fixed at 400 A for In ? 40 A,

adjustable from 6.5 to 13 In for In = 50 A,

adjustable from 5 to 10 In for In ? 63 A

Equipped with earth leakage module

Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A

Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)

Breaking capacity Icu 36 kA (400 V~)

4P

In : 16 A

Caracteristici generale

DPX³ 250 HP - thermal magnetic release MCCBs from 16 to 250 A - fixing on plate

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Furnizat cu: screws for connections, fixing screws, and insulated shileds (phase barriers)

Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable

Can be mounted on plate in XL³ and XL³ S cabinets and enclosures

Conform to IEC 60947-2

Pret: 2.152,21 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-tip-usol250-hp-thermal-magnetic-mccb-cu-electronic-earth-leakage-module-fixed-version-36ka-4p-16a-228858>