



LEGRAND* INTRERUPATOR GENERAL TIP USOL250 HP THERMAL MAGNETIC RELEASE MCCB FIXED VERSION - PUTERE DE RUPERE 100KA - 3P - 125A

Caracteristici tehnice

MCCBs - fixed version

Thermal adjustable from 0.8 to 1 In

Magnetic:

fixed at 400 A for In $\geq$ 40 A,

adjustable from 6.5 to 13 In for In = 50 A,

adjustable from 5 to 10 In for In $\geq$ 63 A

Breaking capacity Icu 100 kA (400 V~)

3P

In : 125 A

Caracteristici generale

DPX³ 250 HP - thermal magnetic release MCCBs from 16 to 250 A - fixing on plate

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Furnizat cu: screws for connections, fixing screws, and insulated shileds (phase barriers)

Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable

Can be mounted on plate in XL³ and XL³ S cabinets and enclosures

Conform to IEC 60947-2

Pret: 978,29 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-tip-usol250-hp-thermal-magnetic-release-mccb-fixed-version-putere-de-rupere-100ka-3p-125a-228882>