



## **LEGRAND\* INTRERUPATOR GENERAL TIP USOL250 HP THERMAL MAGNETIC RELEASE MCCB FIXED VERSION - PUTERE DE RUPERE 100KA - 3P - 50A**

Caracteristici tehnice

MCCBs - fixed version

Thermal adjustable from 0.8 to 1 In

Magnetic:

fixed at 400 A for In ? 40 A,

adjustable from 6.5 to 13 In for In = 50 A,

adjustable from 5 to 10 In for In ? 63 A

Breaking capacity Icu 100 kA (400 V~)

3P

In : 50 A

Caracteristici generale

DPX<sup>3</sup> 250 HP - thermal magnetic release MCCBs from 16 to 250 A - fixing on plate

Moulded case MCCBs for switching, control isolation and protection of low Tensiune electrical lines

Can be fitted with auxiliaries

Furnizat cu: screws for connections, fixing screws, and insulated shileds (phase barriers)

Can be fitted with cage terminals 120 mm<sup>2</sup> max. (flexible cable) or 150 mm<sup>2</sup> max. rigid cable

Can be mounted on plate in XL<sup>3</sup> and XL<sup>3</sup> S cabinets and enclosures

Conform to IEC 60947-2

Pret: 978,29 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-tip-usol250-hp-thermal-magnetic-release-mccb-fixed-version-putere-de-rupere-100ka-3p-50a-228891>