

LEGRAND* KEOR T EVO ON-LINE DOUBLE CONVERSION UPS - THREE PHASE VFI SS 111 - 20 KW - BACKUP TIME 0 MIN

Caracteristici tehnice
UPS
Nominal Putere: : 20 kW
Backup time: : 0 min
Dimensions (H x W x D): : 1020 x 265 x 800 mm
Net weight: : 84 kg
Caracteristici generale
KEOR T EVO - On-line double conversion UPS (tower) - three phase VFI SS 111
For civil, commercial, industrial automation and IT applications requiring small three phase Putere (up to 20 kVA) with standard back up time in compact footprint
Installation: downstream Putere generators. 3 level IGBT inverter
DSP advanced control logic
Putere factor: 1 (kVA = kW). Efficiency up to 95%
Internal Batteries
Touch Screen Display
Parallel connection possible: up to 4 UPSs. Dedicated input bypass line. Embedded manual bypass
Full connectivity with RS232, RS485 (ModBus), 4xDry contacts, Net Interface Slot (SNMP), EPO, Generator Friendly port
Equipped with wheels for easy moving of the UPS
Pret: 57.953,02 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/keor-t-evo-on-line-double-conversion-ups-three-phase-vfi-ss-111-20-kw-backup-time-0-min-229337