



LEGRAND LIGHTING MANAGEMENT-TRAFFIC DETECTION-CEILING MOUNTING- IR - 270° - RANGE 18 M

Caracteristici tehnice

Ideal for outdoor and humid areas

PIR IP 55 wall or ceiling-mounting Lighting Management sensor, 270°

Multi lens sensor with directional head, range 18 m

Recommended fixing height: 2.5 m

3-wire with neutral

Standby Consum: 0.7 W

Can be mounted on an angle using accessory Cat.No 0 489 72

Caracteristici generale

Lighting Management sensors for 1 circuit - Lighting Management sensors for passage areas with natural light

Check presence and natural light level continuously, switch off when there is sufficient natural light

Occupancy mode (automatic switch-on/off factory setting)

Can be used with push-button Cat.No 0 770 40 (or illuminated push-button Cat.No 0 770 33) for vacancy mode (manual switch-on and manual or automatic switch-off)

Precise on-site adjustment using configuration tool Cat.No 0 882 30

Adjustable time delay: 5 s to 59 min

Light level threshold adjustable from 5 to 1275 lux

Pret: 1.404,40 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lighting-management-traffic-detection-ceiling-mounting-ir-2700-range-18-m-229753>