

LEGRAND LIGHTING MANAGEMENT--WALL MOUNTING-DT-360°-PENTRU 93 M² AREAS - FLUSH MOUNTING

Caracteristici tehnice
Ideal for working areas
Dual technology ceiling-mounting Lighting Management sensor, 360°
Infrared and ultrasonic detection, range O8 m
Recommended fixing height: 2.50 m
IP 20
Optimum distance between 2 sensors: 6 m
Consum: 0.5 W on standby
Fixes directly to a false ceiling with mounting claws (included) or installed in a Batibox box, depth 50 mm
Can be surface-mounted on ceiling using accessory Cat. No 0 488 75
Caracteristici generale
Lighting Management sensors for managing several circuits - Lighting Management sensors for controllers for passage areas and working areas with natural light
Check presence and light level continuously, switch off when there is sufficient natural light
Automatic switch-on/off (factory setting)
Precise on-site adjustment using configuration tool
Connect to controllers by cord or RJ 45 cable or BUS/SCS cable to be fitted with RJ 45 connector Cat.No 0 488 72
Pret: 539,54 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lighting-management-wall-mounting-dt-3600-pentru-93-m2-areas-flush-mounting-229755