



LEGRAND LIGHTING MANAGEMENT--WALL MOUNTING-DT-360°-PENTRU 93 M² AREAS - FLUSH MOUNTING

Caracteristici tehnice

Ideal for working areas

Dual technology ceiling-mounting Lighting Management sensor, 360°

Infrared and ultrasonic detection, range 08 m

Recommended fixing height: 2.50 m

IP 20

Optimum distance between 2 sensors: 6 m

Consum: 0.5 W on standby

Fixes directly to a false ceiling with mounting claws (included) or installed in a Batibox box, depth 50 mm

Can be surface-mounted on ceiling using accessory Cat. No 0 488 75

Caracteristici generale

Lighting Management sensors for managing several circuits - Lighting Management sensors for controllers for passage areas and working areas with natural light

Check presence and light level continuously, switch off when there is sufficient natural light

Automatic switch-on/off (factory setting)

Precise on-site adjustment using configuration tool

Connect to controllers by cord or RJ 45 cable or BUS/SCS cable to be fitted with RJ 45 connector Cat.No 0 488 72

Pret: 534,66 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lighting-management-wall-mounting-dt-3600-pentru-93-m2-areas-flush-mounting-229755>