



LEGRAND MODUL DE MASURA CX³ - CONEXIUNE DIRECTA PANA LA 63A - 3-PHASE + 3 COILS - 1 MODULE

Caracteristici tehnice

Measurement module

For measuring current, Tensiune, active/reactive Putere and other values

Conform to IEC/EN 61557-12

Accuracy: class 0.5

Direct connection up to 63 A with closed Rogowski coils

Allow the passage of prong-type supply busbars (upper side)

Supplied with closed Rogowski coils

Enables upstream busbar connection

3-phase measuring module and closed

Rogowski coil up to 63 A

Consum: 0.418 W - 34.8 mA (12 V =)

Numar de module : 1

Caracteristici generale

CX³ energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 1.184,21 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/modul-de-masura-cx3-conexiune-directa-pana-la-63a-3-phase-3-coils-1-module-230597>