



LEGRAND* MODUL DE MASURA CX³ CONEXIUNE DIRECTA CU OPEN FLEXIBLE ROGOWSKI COIL - 3-PHASE + 3 COILS PANA LA 3200A

Caracteristici tehnice

Measurement module

For measuring current, Tensiune, active/reactive Putere and other values

Conform to IEC/EN 61557-12

Accuracy: class 0.5

Direct connection with open, flexible Rogowski coils

Allow the passage of prong-type supply busbars (upper side)

Supplied with opened, flexible Rogowski coils and fixing supports for busbars

3-phase measuring module + 3 coils up to 3200 A

Consum: 0.418 W - 34.8 mA (12 V =)

Numar de module : 1

Caracteristici generale

CX³ energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 4.282,55 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modul-de-masura-cx3-conexiune-directa-cu-open-flexible->

rogowski-coil-3-phase-3-coils-pana-la-3200a-230601