

LEGRAND* MONTAJ INCASTRAT FRAME URA ONE - PENTRU VERTICAL SIGNALLING PLATE CAT.NO 6 616 64

Caracteristici tehnice
Accessories
Montaj incastrat frame
Special frame with vertical signalling plate
Caracteristici generale
URA ONE - indoor self-contained emergency lighting luminaire LED
LED non-maintained and maintained units
Certified to IEC and EN 60598-2-22 standards
High Putere LEDs with optimized lighting distribution
Low Consum switching Tensiune de alimentare. Fully recyclable
Plug-in back with pre-cutted holes grid to ease installation and maintenance
Automatic terminals with high capacity: 2 x 2.5mm². IP 42 - IK 07
Duration: 1 and 3 hours. Ni-Cd or Ni-MH batteries. Recharge time: 24 hours. Charge monitor with a green LED. Opal diffuser
Tensiune de alimentare: 230 V~ ± 10% - 50/60 Hz. Class II
Flat Montaj incastrat integration into ceiling and wall with Montaj incastrat frame Cat.Nos 6 616 50/51
Decorative frame to enhance surface-mounting aesthetic integration Cat.Nos 6 616 54/55
Pret: 73,09 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/montaj-incastrat-frame-ura-one-pentru-vertical-signalling-plate-cat-no-6-616-64-230642