

LEGRAND* SENZOR DE MISCARE CUOUT NEUTRAL VALENA LIFE - CU CAPAC - ALB

Caracteristici tehnice
Motion sensors
All sensors are compatible with any type of lamp
Detection field 120°
Detection range 8 m
Integrated self-protection against overloads and short-circuits
Motion sensors without neutral
Accepted Putere by lamp type:
LEDs 3 W to 100 W (If several sensors are installed on the same circuit, the minimum load increases)
compact fluorescent 3 W to 100 W (If several sensors are installed on the same circuit, the minimum load increases)
LEDs, CFLs, Halogen, fluorescent tubes with ferromagnetic or electronic ballast: 3 VA to 250 VA
230 V halogen, incandescent: 3 W to 250 W
Up to 3 sensors can be connected in parallel
Time delay setting from 10 s to 10 min
Light level threshold setting from 5 lux to 1275 lux
Standby Consum: 0.02 W
White
Caracteristici generale
Valena™ Life - motion sensors, roller blind controls and thermostats with cover plate
Valena In'Matic mechanisms supplied with cover plates and support frames
To be equipped with plates
Supplied with mounted dust protection transparent shield
Flowpack packaging: robust protection to ensure optimum operation
Pret: 555,20 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/senzor-de-miscare-cuout-neutral-valena-life-cu-capac-alb-230678