



LEGRAND* ON-LINE DOUBLE CONVERSION UPS - 6000 VA - 5400 W- BACKUP TIME 22 MIN

Caracteristici tehnice

UPS

The stated backup time in minutes is estimated and may vary according to the load characteristics, operating conditions and environment

Nominal Putere: : 6000 VA

Active Putere: : 5400 W

Backup time: : 22 min

Weight: : 106 kg

Caracteristici generale

Keor S - On-line double conversion UPS (tower) - single phase

For industrial environment (food industry, laboratories ...) or applications requiring long backup time (electro-medical ...)

Installation: downstream Putere generators. Possibility to add batteries for extended autonomy. Parallel connection possible: up to 4 UPSs. Advanced management depending on the battery discharge level

Sinusoidal output

LCD screen

Self-diagnosis

Putere factor: 0.9

Integrated automatic bypass and maintenance bypass. Integrated slot for installing a communication interface for Ethernet network connection, to be ordered separately

Cold Start Function. Microprocessor control

Telephone line/Internet (RJ 11/RJ 45)

Remote emergency shutdown function ("Emergency Putere Off" - EPO). Equipped with 4 wheels for easy moving of the UPS

Pret: 21.930,87 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/on-line-double-conversion-ups-6000-va-5400-w-backup-time-22-min-230972>