



LEGRAND* ON-LINE DOUBLE CONVERSION UPS - TOWER - 2000 VA - 1800 W

Caracteristici tehnice

UPS with IEC sockets

The stated backup time in minutes is estimated and may vary according to the load characteristics, operating conditions and environment

Nominal Putere: : 2000 VA

Active Putere: : 1800 W

Backup time: : 5 min

No. of sockets IEC (10 A): : 6

Weight: : 17 kg

Caracteristici generale

Keor LP - On-line double conversion UPS (tower) - single phase VFI

For security systems, lighting systems, CCTV, servers. Ideal for environments with frequent electrical disturbances

Installation: downstream Putere generators. Advanced management depending on the battery discharge level

Self-diagnosis. Putere factor: 0.9

Automatic internal bypass, manual bypass for external maintenance (optional)

Integrated slot for installing a communication interface for Ethernet network connection, to be ordered separately

Cold Start function

Microprocessor control

Telephone line/Internet protection (RJ 11/RJ 45)

Internal network interface Cat.No 3 108 82 for remote protection of equipment and systems

Remote emergency shutdown function ("Emergency Putere Off" - EPO)

Pret: 4.013,96 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/on-line-double-conversion-ups-tower-2000-va-1800-w-230974>