

LEGRAND* ON-LINE DOUBLE CONVERSION UPS - TOWER - 2000 VA - 1800 W

Caracteristici tehnice
UPS with IEC sockets
The stated backup time in minutes is estimated and may vary according to the load characteristics, operating conditions and environment
Nominal Putere: : 2000 VA
Active Putere: : 1800 W
Backup time: : 5 min
No. of sockets IEC (10 A): : 6
Weight: : 17 kg
Caracteristici generale
Keor LP - On-line double conversion UPS (tower) - single phase VFI
For security systems, lighting systems, CCTV, servers. Ideal for environments with frequent electrical disturbances
Installation: downstream Putere generators. Advanced management depending on the battery discharge level
Self-diagnosis. Putere factor: 0.9
Automatic internal bypass, manual bypass for external maintenance (optional)
Integrated slot for installing a communication interface for Ethernet network connection, to be ordered separately
Cold Start function
Microprocessor control
Telephone line/Internet protection (RJ 11/RJ 45)
Internal network interface Cat.No 3 108 82 for remote protection of equipment and systems
Remote emergency shutdown function ("Emergency Putere Off" - EPO)
Pret: 4.051,30 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/on-line-double-conversion-ups-tower-2000-va-1800-w-230974