

LEGRAND* ON-LINE DOUBLE CONVERSION UPS - CU ISOLATION - 6000 VA - 5400 W

Caracteristici tehnice
UPS with isolation transformer
The stated backup time in minutes is estimated and may vary according to the load characteristics, operating conditions and environment
Nominal Putere: : 6000 VA
Active Putere: : 5400 W
Backup time: : 0 min
Weight: : 100 kg
Caracteristici generale
Keor S - On-line double conversion UPS (tower) - single phase
For industrial environment (food industry, laboratories ...) or applications requiring long backup time (electro-medical ...)
Installation: downstream Putere generators. Possibility to add batteries for extended autonomy. Parallel connection possible: up to 4 UPSs. Advanced management depending on the battery discharge level
Sinusoidal output
LCD screen
Self-diagnosis
Putere factor: 0.9
Integrated automatic bypass and maintenance bypass. Integrated slot for installing a communication interface for Ethernet network connection, to be ordered separately
Cold Start Function. Microprocessor control
Telephone line/Internet (RJ 11/RJ 45)
Remote emergency shutdown function ("Emergency Putere Off" - EPO). Equipped with 4 wheels for easy moving of the UPS
Pret: 22.000,69 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/on-line-double-conversion-ups-cu-isolation-6000-va-5400-

w-230978