

LEGRAND PANOU MONTAJ PRIZA PRISINTER HYPRA - IP44 - 380/415 V~ -16 A - 3P+E -PLASTIC

Caracteristici tehnice
LV prisinters
Dust resistance IP may be increased by rubber push-button (on request) - IP 55 cover closed or connected - IP 44 connected
380 to 415 V~ 50/60 Hz - 16 A 3P+E
To be associated with surface-mounting box Cat. No 0 520 49 for surface-mounting socket
Panel mounting socket - plastic
16 A
Caracteristici generale
Hypra IP 44 sockets and plugs metal, plastic, rubber, IP 44/55 Prisinter - LV 16 to 63 A and ELV 16 and 32 A
Conform to IEC 60309-1 and IEC 60309-2
IP 44 according to IEC 60529
IK 09: plastic and rubber
IK 10: metal according to IEC 62262
Self-extinguishing:
850°C (support of active parts) / 960 °C for Prinsinter)
650 °C: plastic housing conform to IEC 60695-2-10
50°C to + 100°C (- 20°C for Prisinter)
Pret: 701,22 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/panou-montaj-priza-prisinter-hypra-ip44-380-415-v-16-a-3p-e-plastic-231314