



### CAVI VENTILATOR TUBULATURA 160MM 140MC/H

Ventilator metalic pentru tubulatura. Scema de montaj si domeniul de aplicare se poate vedea in poza secundara.

Material constructiv - otel

Temperatura maxima de lucru +42 grade celsius

Alimentare la 230V

Grad de protectie IP X2

Sunet 51 Db

Turatie 1400 rotatii / minut

Putere electrica 40W

Flux de aer evacuat 140 mc / ora

| type            | unit | Ø150 | Ø160 | Ø200 | Ø250 | Ø315 |
|-----------------|------|------|------|------|------|------|
| Air flow        | m3/h | 270  | 280  | 350  | 600  | 1000 |
| Static pressure | Pa   | 40   | 50   | 55   | 65   | 75   |

|                      |       |        |        |        |        |        |
|----------------------|-------|--------|--------|--------|--------|--------|
| Static pressure      | mmH2O | 4,08   | 5,1    | 6,12   | 8,15   | 11,01  |
| Acoustic pressure    | dB(A) | 50     | 51     | 54     | 57     | 62     |
| Power supply voltage | V/Hz  | 230/50 | 230/50 | 230/50 | 230/50 | 230/50 |
| Motor rotation       | rpm   | 1400   | 1400   | 1400   | 1400   | 1400   |
| Power                | W     | 40     | 40     | 40     | 86     | 110    |
| Current consumption  | A     | 0,19   | 0,2    | 0,25   | 0,3    | 0,4    |
| Max. Working Temp.   | oC    | 42     | 42     | 42     | 42     | 42     |
| Weight               | kg    | 1,4    | 1,5    | 1,57   | 2,78   | 4,21   |
| IP Code              | IP    | X2     | X2     | X2     | X2     | X2     |
| Insulation class     |       |        |        |        |        |        |

Pret: 0,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ventilator-tubulatura-160mm-140mc-h>