



## **LEGRAND\* PULSE CONCENTRATOR CX<sup>3</sup> - PANA LA 3 PULSE CIRCUITS - 1 MODULE**

Caracteristici tehnice

Pulse concentrator

Enables upstream busbar connection

For collecting and transmitting measurements taken by universal pulse energy meters (water, gas, etc...)

Up to 3 pulse circuits

Consum: 0.288 W - 24 mA (12 V =)

Numar de module : 1

Caracteristici generale

CX<sup>3</sup> energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX<sup>3</sup> energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX<sup>3</sup> and DPX<sup>3</sup>), locally ("Stand alone" ) or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 550,29 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pulse-concentrator-cx3-pana-la-3-pulse-circuits-1-module-232696>