

LEGRAND ROOM CONTROLLER PENTRU DALI AND DSI DIMMING - 1 INPUT - 2 OUTPUTS

Caracteristici tehnice
For controlling 1 or 2 circuits in one room
1 sensor input, 2 inputs for auxiliaries
2 outputs
Can be used with a push-button, including a pushbutton with LED indicator, Cat.Nos 0 770 40/33 for manual switch-on and manual or automatic switch-off
Dimming - DALI ballast
2 DALI outputs (32 ballasts max.) and 1 ventilation output (volt-free contact)
Used to vary the light level on the window side of a room (where there is more natural light) separately from the hallway side
Used to control a maximum of 32 DALI ballasts
Connection via screw terminals
Caracteristici generale
Lighting Management sensors for managing several circuits - multi-circuit ceiling-mounting controllers for areas with natural light
Ceiling-mounting or installation in Cablofil cable trays (see Legrand Cable Management catalogue)
Connection to sensors (Cat.Nos 0 488 20/22/34 and 0 784 85/86, 5 740 46/48) by cord or RJ 45 cable or BUS/SCS cable to be fitted with RJ 45 connector Cat.No 0 488 72
Pret: 1.309,98 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/room-controller-pentru-dali-and-dsi-dimming-1-input-2-outputs-233392