



LEGRAND ROOM CONTROLLER PENTRU DALI AND DSI DIMMING - 1 INPUT - 2 OUTPUTS

Caracteristici tehnice

For controlling 1 or 2 circuits in one room

1 sensor input, 2 inputs for auxiliaries

2 outputs

Can be used with a push-button, including a pushbutton with LED indicator, Cat.Nos 0 770 40/33 for manual switch-on and manual or automatic switch-off

Dimming - DALI ballast

2 DALI outputs (32 ballasts max.) and 1 ventilation output (volt-free contact)

Used to vary the light level on the window side of a room (where there is more natural light) separately from the hallway side

Used to control a maximum of 32 DALI ballasts

Connection via screw terminals

Caracteristici generale

Lighting Management sensors for managing several circuits - multi-circuit ceiling-mounting controllers for areas with natural light

Ceiling-mounting or installation in Cablofil cable trays (see Legrand Cable Management catalogue)

Connection to sensors (Cat.Nos 0 488 20/22/34 and 0 784 85/86, 5 740 46/48) by cord or RJ 45 cable or BUS/SCS cable to be fitted with RJ 45 connector Cat.No 0 488 72

Pret: 1.266,44 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/room-controller-pentru-dali-and-dsi-dimming-1-input-2-outputs-233392>