

# LEGRAND* SIGURANTA AUTOMATA CU PROTECTIE DIFERENTIALA 6000 -10 KA - 4P-400 V~ -32 A -30 MA -TIP A

Caracteristici tehnice
4-pole - 400 V~
4-module RCBOs are compatible with prong-type and fork type supply busbars
7-module RCBOs are compatible with prong-type supply busbars only
A Type 30 mA
C curve
Nominal rating In : 32 A
Numar de module : 4
Caracteristici generale
RCBOs DX³ 6000 - 10 kA - residual current circuit breakers from 10 A to 63 A - AC, A and F types
Conform to IEC 61009-1, IEC 62423 (F type)
Tensiune independent tripping
Breaking capacity:
6000 - IEC 61009-1 - 10 kA / IEC 60947-2 for single pole + neutral, 2 and 4-pole
AC type : detect AC component faults
A type : detect AC and DC component faults
F type (High immunity) : detect AC and pulsating DC residual currents. Enhanced immunity to unwanted tripping in disturbed environments. Detection of high frequency fault currents
Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls
Pret: 772,04 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/siguranta-automata-cu-protectie-diferentiala-6000-10-ka-4p-400-v-32-a-30-ma-tip-a-234505