

LEGRAND* DESCARCATOR SPD - T2 - IMAX 40 KA/POLE - 1P+N - NEUTRAL ON LEFT-HAND SIDE

Caracteristici tehnice
T2 SPDs
SPDs with plug-in module and status indicators:
Green: SPD operational
Orange: plug-in module to be replaced
T2 - Imax 40 kA/pole
SPDs recommended for Putere installations
Up: 1.7 kV - In: 20 kA/pole - Uc: 320 V~
Earthing systems : TT, TNC, TNS
Recommended MCB: DX³ 25 A - C curve
1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by encapsulated spark gaps. Also called 1+1 and 3+1
Numar de poli : 1P+N
Pozitie NUL : Stanga
Remote status monitoring (FS contact) : No
Numar de module : 2
Caracteristici generale
Class II (T2) low Tensiune SPDs
Protection against transient overTensiuness for 230/400 V~ Putere networks (50/60 Hz). SPDs compliant with EN/IEC 61643-11 standards
Recommended for distribution boards
Pret: 289,39 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/descarcator-spd-t2-imax-40-ka-pole-1p-n-neutral-on-left-hand-side-235714