





<u>LEGRAND STAND ALONE CONFIGURATION MODULE CX3 - RAIL MOUNTING - 4</u> <u>MODULE</u>

Caracteristici tehnice

Stand alone configuration module

Rail mounting

Enables upstream busbar connection

Optional module for "stand alone" supervision need

Enables to configure, test and control CX3 energy management system and to visualize supervision data

No computer or IP connection required

Consum: 0.438 W - 36.5 mA (12 V =)

Numar de module : 4 Caracteristici generale

CX³ energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 918,50 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/stand-alone-configuration-module-cx3-rail-mounting-4-module-235816