



## **LEGRAND STAND ALONE CONFIGURATION MODULE CX³ - RAIL MOUNTING - 4 MODULE**

Caracteristici tehnice

Stand alone configuration module

Rail mounting

Enables upstream busbar connection

Optional module for "stand alone" supervision need

Enables to configure, test and control CX³ energy management system and to visualize supervision data

No computer or IP connection required

Consum: 0.438 W - 36.5 mA (12 V =)

Numar de module : 4

Caracteristici generale

CX³ energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone" ) or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 1.025,47 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/stand-alone-configuration-module-cx3-rail-mounting-4-module-235816>