



LEGRAND* STANDARD LUMINAIRES U34 LED - 1H DURATION CU OPAL DIFFUSER **- 250 LM**

Caracteristici tehnice

Standard luminaires - Maintained/Non-maintained (M/NM)

Standard luminaires incorporate an external manual lamp test with testing tool Cat.No 6 612 99

1 h duration with transparent diffuser

250 lm - 1h (LEDs)

Caracteristici generale

U34LED environment friendly - indoor self-contained emergency lighting luminaires LED

LED Maintained/Non-maintained units

High Putere LEDs with specially designed lenses optimizing the lighting distribution

IP 42 - IK 07 - Class II

Tensiune de alimentare: 230 V \pm 10% - 50/60 Hz

Very low Consum switching Tensiune de alimentare - Fully recyclable after removing

Environment friendly Ni-MH batteries

Removable plug-in plate to ease installation and maintenance

Automatic terminals with high capacity: 2 x 2.5 mm²

Charge monitor with a green LED

Can be equipped with metallic protection grids Cat.Nos 0 626 92/93

Pret: 677,29 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/standard-luminaires-u34-led-1h-duration-cu-opal-diffuser-250-lm-235830>