

LEGRAND* STATE REPORTING MODULE CX³ - UNIVERSAL SIGNALLING - 3 LED LIGHTS - 1 MODULE

Caracteristici tehnice
State reporting module
Universal signalling module
Enables upstream busbar connection
Equipped with 3 LED lights: green, red and yellow
Indicates various type of information, according to selected configuration:
contacts position, plugged-in or drawn-out product, etc…
Equipped with DIP switches (on the side) allowing product configuration: selection of information type and of the LED behaviour
Compatible with symmetrical rail mounting protection devices or head equipment (DMX³ and DPX³)
Consum: 0.377 W - 31.4 mA (12 V =)
Numar de module : 1
Caracteristici generale
CX³ energy management system
Conform to IEC/EN 61131-2 (Programmable controllers)
CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely
All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)
Tensiune de alimentare with specific module Cat.No 4 149 45
Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)
Pret: 506,86 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/state-reporting-module-cx3-universal-signalling-3-led-lights-1-module-235847